

# MATERIAL SAFETY DATA SHEET

**SECTION 1 - PRODUCT IDENTIFICATION AND USE** 

Manufacturer's Name: DriTherm International, Inc.

2500 Plaza 5 Address:

Harborside Financial Center

Jersey City, NJ 07311

Product: DriTherm (Modified Calcium Carbonate)

Chemical Formula: CaCO3 Telephone:

(973) 808-2255 (800) 343-4188

Website:

www.dritherm.com

CAS

1317-650-3

**SECTION 2 - HAZARDOUS INGREDIENTS** 

Hazardous Materials Identification System Category Rating

Health Hazard Flammability Hazard 0 Reactivity Hazard Personal Protection

0 Ε

Ingredients Percentage (w/w) **CAS Number Exposure Limits** 

Calcium Carbonate >95-98 1317-650-3 ACGIHTLV: Total Dust 10.0 mg./m3

Respirable dust 5.0 mg / m3

OSHAPEL:

Total dust 15 mg/m3 TWA Respirable dust

5.0 mg/m3 TWA

Magnesium Carbonate 546-93-0 1-2

Silica, quartz <5.0% 1408-60-7 ACGIHTLV: 0.1 mg/m3 respirable OSHAPEL: 0.1 mg/m3 Respirable

This product is surface treated with stearic acid (CAS#57-11-4)

**SECTION 3 - PHYSICAL AND CHEMICAL CHARACTERISTICS** 

Density (dry): 2.71 g/ml Specific Gravity (wet): N/A Reactivity in Water: NONE

Solubility in Water: NEGLIGIBLE Appearance and Odor: WHITE POWDER

**SECTION 4 - FIRE AND EXPLOSION HAZARD DATA** 

Special Firefighting Procedures: NONE Flash Point: NON-FLAMMABLE Unusual Fire and Explosion

Hazards: NONE

**SECTION 5 - REACTIVITY DATA** 

Hazardous Polymerization: WILL NOT OCCUR Stability: STABLE Hazardous Decomposition Products: NONE



# MATERIAL SAFETY DATA SHEET

### **SECTION 6 - TOXICOLOGICAL PROPERTIES AND HEALTH HAZARD DATA**

#### EFFECTS AND HAZARDS OF ACUTE OVEREXPOSURE

Effects and Hazards of Inhalation Can be irritating to the respiratory tract. Symptoms include sneezing and slight nose

irritation.

Effects and Hazards of Eye Contact Mild irritation. Symptoms include watering and irritation.

Effects and Hazards of Skin Contact No effect

Effects and Hazards of Ingestion Ingestion of very large quantities may result in intestinal obstruction and/or constipation.

Considered to be of very low toxicity.

#### EFFECTS AND HAZARDS OF CHRONIC EXPOSURE

IARC found limited evidence for human carcinogenicity of the crystalline silica ingredient only. Limited evidence means a "casual" interpretation is credible, but alternative explanations such as chance, bias or confounding effects could not be adequately excluded. The DriTherm product typically contains less than 5% by weight of crystalline silica. At the present level of expertise of medical research, there is no direct evidence that crystalline silica at these levels in limestones constitutes a health risk.

### **SECTION 7 - PREVENTATIVE MEASURES**

HANDLING If engineering controls and work practices are not effective in controlling exposure to the

material, then wear suitable personal protective equipment including NIOSH or OSHA

approved dust respirators.

STORAGE CONDITIONS

Store in closed containers in a dry place separate from incompatible materials.

SPILL & LEAK PROCEDURES

Respiratory protection should be worn by those in cleanup operation to protect

Respiratory protection should be worn by those in cleanup operation to protect from airborne dust. Measures should be taken to reduce airborne dust during cleanup operations.

Calcium carbonate is not a hazardous material under RCRA and may be disposed of as

industrial waste.

# **SECTION 8 - FIRST AID MEASURES**

TREATMENT FOR INHALATION Remove source of contamination or move victim to fresh air. Obtain medical advice if required.

TREATMENT FOR EYE CONTACT Immediately flush the contaminated eye(s) with lukewarm gently flowing water, for 10 minutes, by the clock, holding the eyelid(s) open. If irritation persists, obtain medical advice

immediately.

TREATMENT FOR SKIN CONTACT If irritation occurs, flush area with lukewarm, gently running water for at least 10-minutes. If irritation persists, obtain medical advice immediately.

TREATMENT FOR INGESTION
(Swallowing)

Never give anything by mouth if victim is rapidly losing consciousness or is unconscious or convulsing. Rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 8 to 10 oz. (240 to 300 ml) of water to dilute material in stomach. Obtain medical advice immediately.

## **SECTION 9 - PREPARATION DATE OF MSDS**

Prepared by: J.S. Sandman Date: June 30, 2011

DISPOSAL

The information contained herein has been compiled by technically knowledgeable personnel from sources which DriTherm International, Inc. considers reliable. This information is accurate to the best of our knowledge. Before using this product the foregoing MSDS and the product label should be read carefully. The information contained herein relates only to the specific material indicated above and does not relate to use in combination with any other material or in any process. Customers are encouraged to conduct their own tests concerning the use of this product as the manner and conditions of use and handling may involve additional considerations. DriTherm International, Inc. assumes no responsibility for any damages, losses, injuries or consequential damages which may result from the use of misuse of this product and the recipient assumes all such risks.