





Protective 5 1 Safety Gloves Glasses

WHMTS Pictograms

Not Controlled

Not Regulated

DOT Pictograms

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Heavy Density Pipe Insulation**

MSDS Manufacturer Number:

18994-NAM

ASJ 25 Pipe Insulation, ASJ/SSL II® Pipe Insulation, Heavy Density Pipe Insulation, No-Wrap Pipe Insulation, Pipeshield, SSL® Pipe Insulation, SSL-II® Pipe Insulation, VaporWick®, Vitro Fibras Pipe Insulation, Evolution™ Paper-Free ASJ, Aislamiento para Tuberia Synonyms:

Product Use/Restriction: Pipe Insulation

Manufacturer Name: Owens Corning Insulating Systems, LLC

One Owens Corning Parkway Toledo, OH 43659 Address:

Customer Service Phone Number:

1-800-GET-PINK or 1-800-438-7465

Health Issues Information:

Canutec:

1-800-GET-PINK or 1-800-438-7465

Technical Product Information:

1-800-GET-PINK or 1-800-438-7465

Emergency Phone Number:

1-419-248-5330 (after 5pm ET and weekends)

CHEMTREC:

800-424-9300 (24 hours everyday) (613) 996-6666 (Canada 24 hours everyday)

Website: www.owenscorning.com

MSDS Creation Date: May 16, 1995

MSDS Revision Date: August 12, 2010

MSDS Format: According to ANSI Z400.1-2004



HMIS Health Hazard 2 Fire Hazard 0 Reactivity Personal X Protection

Chronic Health Effects

Page 1 of 6

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Fiber Glass (Wool)	65997-17-3	60 - 100 by weight	266-046-0
Cured Binder	N/A	0 - 40 by weight	
Non-Hazardous Statement:	small enough quanti disclosure. These cor	onents of this product are non ty as to not meet regulatory th nponents contain no substanc lassification of this product.	resholds for

SECTION 3 - HAZARDS IDENTIFICATION

Applies to Product

Emergency Overview: Exposure to dust may be irritating to eyes, nose, and throat.

Route of Exposure: Eye contact Skin contact Inhalation

Potential Health Effects:

Eye: May cause slight irritation. Skin: May cause slight skin irritation. Inhalation: $\label{eq:maycause} \mbox{May cause irritation of respiratory tract.}$

Ingestion: Ingestion of this product is unlikely.

Chronic Health Effects: There is no known chronic health effect connected with long-term use

or contact with this product.

This product contains a component which is listed by IARC, OSHA or

Heavy Density Pipe Insulation Product Code: 18994-NAM Revision:: 08/12/2010

NTP. See Section 11 for additional information.

Potential Environmental

Effects:

There is no known ecological information for this material.

Aggravation of Pre-Existing Conditions:

Chronic respiratory or skin conditions may temporarily worsen from exposure to this product.

OSHA Regulatory Status: This product is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

SECTION 4 - FIRST AID MEASURES

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the $\,$ Eye Contact:

eyelids with fingers.
Do not rub or scratch eyes.

If eye irritation persists, consult a specialist.

Skin Contact:

Wash off immediately with soap and cold water. DO NOT use warm water because this will open up the pores of the

DO NOT use warm water pecause this will open up the skin, which will cause further penetration of the fibers.
Use a wash cloth to help remove fibers.
DO NOT rub or scratch affected areas.
Remove contaminated clothing.

If irritation persists get medical attention.

Never use compressed air to remove fibers from the skin.

If fibers are seen penetrating from the skin, the fibers can be removed by applying and removing adhesive tape so that the fibers adhere to

the tape and are pulled out of the skin.

Inhalation: Move to fresh air.

If symptoms persist, call a physician.

Ingestion:

Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal

blockage does not occur. Rinse mouth with water and drink water to remove fibers from the

throat.

If symptoms persist, call a physician.

Note to Physicians: Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties: Non Flammable.

Flash Point: Does not apply. Auto Ignition Temperature: Does not apply.

Extinguishing Media: dry chemical

foam

carbon dioxide (CO2)

water fog

Wear self-contained breathing apparatus (SCBA) and full fire fighting

Hydrogen chloride to be released from the PVC barrier and vinyl facings

Unusual Fire Hazards: Hazardous Combustion

Protective Equipment:

Byproducts:

Carbon monoxide. Carbon dioxide

Other undetermined compounds could be released in small quantities.

Universal Fire And Explosion

Not available

NFPA Ratings:

NFPA Health: NFPA Flammability:

NFPA Reactivity:

NFPA Other:

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Avoid contact with skin and eyes.

Environmental Precautions: Prevent further leakage or spillage if safe to do so.

This material will settle out of the air. Methods for containment:

Prevent from spreading by covering, diking or other means.

Use an industrial vacuum cleaner with a high efficiency filter to clean up Methods for cleanup:

dust and fiber contamination. Avoid dry sweeping.

Pick up and transfer to properly labeled containers.

Other Precautions: Does not apply.

Heavy Density Pipe Insulation Product Code: 18994-NAM Revision: 08/12/2010

SECTION 7 - HANDLING and STORAGE

Handling: Avoid dust formation.

Do not breathe dust. Wear personal protective equipment.

Keep product in its packaging until use to minimize potential dust Storage:

generation.

Product should be kept dry and undercover.

Hygiene Practices: Wash hands before breaks and immediately after handling the product.

Remove and wash contaminated clothing before re-use

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: Provide local exhaust and/or general ventilation to maintain exposure

below regulatory and recommended limits.

Dust collection system must be used in transferring operations, cutting or machining or other dust generating processes, such as using power

Vacuum or wet clean-up methods should be used.

Eye/Face Protection: Safety glasses with side-shields.

Skin Protection Description: Protective gloves.

Long sleeved shirt and long pants.

Respiratory Protection:

When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.

Other Protective:

When the temperature of the surface being insulated exceeds 250°F (121°C), including initial startup, the binder in these products may undergo various degrees of decomposition depending on the temperature in the application.

The need for respiratory protection will vary according to the airborne concentration of the decomposition products released and accumulated in the area

Wear the appropriate respiratory protection according to the conditions and exposure levels in the area

Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing before re-use.

General Hygiene Considerations:

EXPOSURE GUIDELINES

Ingredient	Guideline OSHA	Guideline ACGIH	Ontario Canada	Mexico	
Fiber Glass (Wool)	PEL-TWA: 1 f/cc (Respirable)		TWAEV-TWA: 0.05 mg/m3 or 1 f/cc STEL: 0.6 mg/m3	TWA: 0.15 mg/m3	

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Tan with or without jacket of paper or aluminized plastic film. Physical State Appearance:

Color:

Odor: Faint resin odor.

Boiling Point: No Data Melting Point: No Data Specific Gravity: No Data

Solubility: Insoluble in water.

Vapor Density: No Data Vapor Pressure: No Data Evaporation Rate: No Data pH: No Data Viscosity: No Data Does not apply. Auto Ignition Temperature: Does not apply.

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to Avoid: None expected

Incompatible Materials: No materials to be especially mentioned.

Special Decomposition See Section 5 of MSDS for hazardous decomposition products during a

Heavy Density Pipe Insulation Product Code: 18994-NAM Revision:: 08/12/2010

Products: fire.

SECTION 11 - TOXICOLOGICAL INFORMATION

Applies to Product:

Acute Toxicity:

Dusts may cause mechanical irritation to eyes and skin. Ingestion may cause transient irritation of throat, stomach and gastrointestinal tract. Inhalation may cause coughing, nose and throat irritation, and sneezing. High exposures may cause difficulty breathing, congestion, and chest tightness.

Carcinogens:							
	ACGIH	NIOSH	OSHA	IARC	NTP	Canada	MEXICO
Fiber Glass (Wool)	A3 Animal Carcinogen	No Data	No Data	Group 3 - Not Classifiable as to its Carcinogenicity to Humans.	glass wool is not		A3 Animal Carcinogen
Cured Binder	No Data	No Data	No Data	No Data	No Data		No Data

Applies to Product:

Sensitization: No information available. Mutagenicity: No information available. Reproductive Toxicity: No information available. Teratogenicity: No information available. Neurological Effects: No information available.

Fiber Glass (Wool):

Chronic Effects:

In October 2001, the International Agency for Research on Cancer (IARC) classified fiber glass wool as Group 3,"not classifiable as to its carcinogenicity to humans". The 2001 decision was based on human studies and animal research that have not shown an association between inhalation exposure to dust from fiber glass wool and the development of respiratory disease. This classification replaces the IARC finding in 1987 of a Group B designation "possibly carcinogenic to humans" humans."

In May 1997, the American Conference of Governmental Industrial Hygienists (ACGIH) adopted an A3 carcinogen classification for glass wool fibers. The ACGIH A3 classification considers glass wool to be carcinogenic in experimental animals at relatively high doses, by routes of administration, at sites, or by mechanisms that it does not consider relevant to worker exposure. It also reviewed the available epidemiological studies and concluded that they do not confirm an increased risk of cancer in exposed humans. Overall, the ACGIH found that the available medical/scientific evidence suggests that glass wool is not likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure.

In 1994, the National Toxicology Program (NTP) classified glass wool (respirable size) as ""reasonably anticipated to be a human carcinogen"". This classification was primarily based upon the 1987 IARC classification. NTP is currently considering reclassifying this material.

Cured Binder:

Inaestion:

Ingestion - Rat LD50: 7 gm/kg - [Autonomic Nervous System - Other (direct) parasympathomimetic Behavioral - Muscle weakness Lungs, Thorax, or Respiration - Respiratory depression](RTECS)

Acute Toxicity

SECTION 12 - ECOLOGICAL INFORMATION

Applies to Product:

Ecotoxicity: This material is not expected to cause harm to animals, plants or fish.

Environmental Stability: Not available Environmental Fate: Not available Bioaccumulation: Not available. Biodegradation: Not available. Mobility In Environmental Not available. Media:

SECTION 13 - DISPOSAL CONSIDERATIONS

Applies to Product :

Waste Disposal: Dispose of in accordance with Local, State, Federal and Provincial

regulations.

Heavy Density Pipe Insulation Product Code: 18994-NAM Revision:: 08/12/2010

Contaminated Packaging: Empty containers should be taken for local recycling, recovery or waste

RCRA Number: No EPA Waste Numbers are applicable for this product's components.

RCRA Characteristics: This material is not expected to be a characteristic hazardous waste under $\ensuremath{\mathsf{RCRA}}.$

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name: Not Regulated. IATA Shipping Name: Not Regulated. Canadian Shipping Name: Not Regulated. IMDG Shipping Name : Not Regulated. ADR Shipping Name: Not Regulated. RID Shipping Name : Not Regulated. ICAO Shipping Name: Not Regulated. MEX Shipping Name : Not Regulated.

SECTION 15 - REGULATORY INFORMATION

Inventory Status

	Japan ENCS	EINECS	China	China	South Korea
	Japan ENCS	Number		KECL	
Fiber Glass (Wool)	Not listed	266-046-0	Listed	Listed	KE-17630
Cured Binder	Not listed			Listed	KE-35185

	Australia AICS	Canada DSL	TSCA Inventory	
			Status	
Fiber Glass (Wool)	Listed	Listed	Listed	
Cured Binder	Listed	Listed	Listed	

Applies to Product:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations. Canada Reg. Status:

Canada WHMIS: Not controlled.

CA PROP 65: The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the State of California to cause cancer.

This product does not contain any chemicals which are subject to the reporting requirements of the Superfund Amendments and SARA:

Reauthorization Act of 1986 (SARA) Title III (40CFR, Part 372).

Section 311/312 Hazard

Categories Acute Health Hazard: Yes

Chronic Health Hazard: Risk of ignition: Sudden Release of Pressure Hazard: Reactive Hazard: Yes No Nο

Clean Air Act: This product does not contain any Hazardous Air Pollutants (HAPs).

Fiber Glass (Wool):

266-046-0 EC Number:

State Right To Know

State ragine to ran					
	RI	MN	IL	PA	MA
Fiber Glass (Wool)	Listed	Listed	Listed	Listed	Listed
Cured Binder	No Data				

	NJ		
Fiber Glass (Wool)	No Data		
Cured Binder	No Data		

SECTION 16 - ADDITIONAL INFORMATION

HMIS Health Hazard:

Heavy Density Pipe Insulation

Revision:: 08/12/2010

HMIS Fire Hazard: 1
HMIS Reactivity: 0
HMIS Personal Protection: X

MSDS Creation Date: May 16, 1995

MSDS Revision Date: August 12, 2010

MSDS Revision Notes: Format Update

Copyright© 1996-2011 Actio Corporation. All Rights Reserved.

Heavy Density Pipe Insulation Product Code: 18994-NAM Revision:: 08/12/2010