

Version 3. Print Date 12/22/2011

REVISION DATE: 12/20/2011

SECTION 1 - PRODUCT IDENTIFICATION / PREPARATION INFORMATION

Product Information

Trade name : TREMSTOP IA RUST RED - 5 GAL

Product code : 937860 805

Supplier : Tremco Canada division

220 Wicksteed Avenue Toronto, ON M4H 1G7

Telephone : (416) 421-3300 Emergency Phone: : (613) 996-6666

Product use : Sealant

Preparation Information

Prepared by: : Sewnauth Raghunandan

Date: : 12/20/2011 Telephone : (416) 421-3300

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Red. Non-sag gunnable paste. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.

Eyes : Slightly irritating.

Ingestion : May cause irritation to the mouth, throat and stomach.

Skin : Irritant effect may be delayed.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

The International Agency for Research on Cancer (IARC) has classified ceramic fiber, fibrous glasswool, and mineral wool (rockwool and slagwool) as possible human carcinogens (Group 2B) based on sufficient evidence of carcinogenicity in animals but insufficient data in humans. In the National Toxicology Program's (NTP) 7th Annual Report on Carcinogens (1994), respirable glasswool was classified as reasonably anticipated to be carcinogenic. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. OSHA considers fibrous glass dust a nuisance dust. Fibrous glass can cause dermatitis, local irritation. Long term overexposure to propylene glycol caused liver abnormalities, kidney damage in laboratory animals. Repeated excessive ingestion may cause central nervous system effects. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3: HAZARDOUS INGREDIENTS



1/5 937860 805



Version 3. Print Date 12/22/2011

REVISION DATE: 12/20/2011

Chemical Name	CAS-No.	Weight % Range	
Fibrous Glass	65997-17-3	1.0 - 5.0	
Amorphous silica	7631-86-9	1.0 - 5.0	
Propylene glycol	57-55-6	1.0 - 5.0	
Melamine	108-78-1	0.5 - 1.5	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1.0	

The ingredients listed above are hazardous as defined in the controlled products regulation. (CPR).

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get

medical attention.

Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.

Skin contact : Wash with water. If irritation, rash or other disorders develop, get medical attention

immediately.

Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control

Center or Physician immediately.

SECTION 5: FIRE / EXPLOSION HAZARDS

Flash point : Not available. Method : Not available.

Burning rate : Non-flammable solid

Lower explosion limit : Not available.

Upper explosion limit : Not available.

Autoignition temperature : Not available.

Extinguishing media : This product is not expected to burn under normal conditions of use. Use

that which is appropriate to the surroundings.

Hazardous combustion

products

Smoke, fumes.

Protective equipment for

firefighters

Not applicable. Product is not expected to burn.

Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - SPILLS / LEAKS / ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal. Keep out of water courses.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not use in confined or poorly ventilated areas. Store in sealed containers in a dry, ventilated warehouse location above freezing.





Version 3. Print Date 12/22/2011

REVISION DATE: 12/20/2011

SECTION 8 - PREVENTIVE MEASURES/EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection equipment

Respiratory protection : Not required under normal conditions of use.

Hand protection : Protect hands with impervious gloves.Eye protection : Use safety glasses if eye contact is likely.

Protective measures : Use professional judgment in the selection, care, and use. Other equipment

not normally required.

Engineering measures : General ventilation is sufficient. Use local exhaust when the general

ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Fibrous Glass	65997-17-3	Ontario TWAEV: ACGIH TWA: Ontario TWAEV: Ontario TWAEV:	5 mg/m3 5 mg/m3 1 ppm 0.5 ppm	Inhalable Inhalable fraction. Respirable fibers Respirable fibers
Amorphous silica	7631-86-9	Ontario TWAEV: Ontario TWAEV: ACGIH TWA: ACGIH TWA: Ontario TWAEV:	3 mg/m3 10 mg/m3 3 mg/m3 10 mg/m3 10 mg/m3	Respirable particles. Inhalable particulate. Respirable particles. Inhalable particles.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	Ontario TWAEV: ACGIH TWA:	0.10 mg/m3 0.025 mg/m3	Respirable fraction. Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State : Paste

Form : Non-sag gunnable paste

Color : Red
Odor : Acrylate
pH : 7.0 - 10.0
Vapour pressure : Not available.
Vapor density : Heavier than air
Melting point/range : 32 ♥, 0 ♥

Freezing point/range : 32 +, 0 ℃

Freezing point : Not available.

Boiling point/range : 212 +, 100 ℃

Water solubility : Miscible

Evaporation Rate: : Not available.

Specific Gravity : 1.45 % Volatile Weight : 30 %



Version 3. Print Date 12/22/2011

REVISION DATE: 12/20/2011

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Oxidizing agents. Strong acids. Strong bases.

SECTION 11 - TOXICOLOGICAL INFORMATION

Amorphous silica, CAS-No.: 7631-86-9

Acute oral toxicity (LD-50 oral) 22,500 mg/kg (Rat) 15,000 mg/kg (Mouse)

Propylene glycol, CAS-No.: 57-55-6

Acute oral toxicity (LD-50 oral) 30,000 mg/kg (Rat) 18,000 mg/kg (Rabbit) 19,000 mg/kg

(Dog) 23,900 - 31,800 mg/kg (Mouse) 18,400 - 196,000

mg/kg (Guinea pig)

Melamine, CAS-No.: 108-78-1

Acute oral toxicity (LD-50 oral) 4,550 mg/kg (Mouse) 3,160 mg/kg (Rat) 3,850 mg/kg (

Rat)

Acute dermal toxicity (LD-50 dermal) 1,000 mg/kg (Rabbit)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Disposal Method : Dispose as hazardous waste according to all local, state, federal and provincial

regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:

NOT REGULATED

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

4/5



Material Safety Data Sheet



TREMSTOP IA RUST RED - 5 GAL

Version 3. Print Date 12/22/2011

REVISION DATE: 12/20/2011

Canadian Regulations:

WHMIS Classification : D2A, D2B

This is a "controlled product" under the Canadian Workplace Hazardous Materials Information System

(WHMIS).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Other Regulations:

Regulatory VOC (less water and : 16 g/l

exempt solvent)

SECTION 16 - OTHER INFORMATION

HMIS Rating:

Health	1	0 = Minimum
Flammability	0	1 = Slight
Reactivity	0	2 = Moderate
PPE		3 = Serious
		4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Sewnauth Raghunandan

Legend

ACGIH - American Conference of Governmental Hygienists OSHA - Occupational Safety and Health Administration

DOT - Department of Transportation PEL - Permissible Exposure Limit

DSL - Domestic Substance List RCRA - Resource Conservation and Recovery Act

EPA - Environmental Protection Agency

STEL - Short Term Exposure Limit

HMIS - Hazardous Materials Information System TLV - Threshold Limit Value IARC - International Agency for Research on Cancer TSCA - Toxic Substances Control Act

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

TWA - Time Weighted Average

V - Volume

NIOSH - National Institute for Occupational Safety and Health VOC - Volatile Organic Compound

NTP - National Toxicology Program WHMIS - Workplace Hazardous Materials Information System



5/5 937860 805