

	Personal Protective Equipment	IATA Pictograms	
	* ~	Not Regulated	
	Protective Safety Gloves Glasses		
ECTION 1 - IDENTIFIC	CATION	<u></u>	4
Product Name:	Heavy Density Pipe Insula	tion	
SDS Manufacturer Number:	18994-SAM-EN		
Synonyms:	ASJ 25 Pipe Insulation, ASJ/SSL II® Pipe Insulation, Heavy Density Pipe Insulation, No-Wrap Pipe Insulation, Pipeshield, SSL® Pipe Insulation, SSL-II® Pipe Insulation, VaporWick®, Vitro Fibras Pipe Insulation, Evolution™ Paper-Free ASJ, Aislamiento para Tuberia		
	Pipeshield, SSL® Pipe Insu Insulation, VaporWick®, Vi	lation, SSL-II® Pipe tro Fibras Pipe Insulat	ion,
Product Use/Restriction:	Pipeshield, SSL® Pipe Insu Insulation, VaporWick®, Vi	lation, SSL-II® Pipe tro Fibras Pipe Insulat	ion,
Product Use/Restriction: Manufacturer Name:	Pipeshield, SSL® Pipe Insu Insulation, VaporWick®, Vi Evolution™ Paper-Free ASJ,	lation, SSL-II® Pipe tro Fibras Pipe Insulat Aislamiento para Tub	ion,
	Pipeshield, SSL® Pipe Insu Insulation, VaporWick®, Vi Evolution™ Paper-Free ASJ, Pipe Insulation	ilation, SSL-İI® Pipe tro Fibras Pipe Insulat Aislamiento para Tub Systems, LLC	ion,
Manufacturer Name:	Pipeshield, SSL® Pipe Insu Insulation, VaporWick®, Vi Evolution [™] Paper-Free ASJ, Pipe Insulation Owens Corning Insulating S One Owens Corning Parkwa	lation, SSL-İI® Pipe tro Fibras Pipe Insulat Aislamiento para Tub Systems, LLC	ion, ieria NFPA
Manufacturer Name: Address: Customer Service Phone	Pipeshield, SSL® Pipe Insu Insulation, VaporWick®, Vi Evolution [™] Paper-Free ASJ, Pipe Insulation Owens Corning Insulating S One Owens Corning Parkwa Toledo, OH 43659	lation, SSL-İI® Pipe tro Fibras Pipe Insulat Aislamiento para Tub Systems, LLC IY 138-7465	ion, ieria NFPA
Manufacturer Name: Address: Customer Service Phone Number: Health Issues	Pipeshield, SSL® Pipe Insu Insulation, VaporWick®, Vi Evolution™ Paper-Free ASJ, Pipe Insulation Owens Corning Insulating S One Owens Corning Parkwa Toledo, OH 43659 1-800-GET-PINK or 1-800-4	ilation, SSL-İI® Pipe tro Fibras Pipe Insulat Aislamiento para Tub Systems, LLC 19 138-7465	ion, ieria NFPA
Manufacturer Name: Address: Customer Service Phone Number: Health Issues Information: Technical Product	Pipeshield, SSL® Pipe Insu Insulation, VaporWick®, Vi Evolution [™] Paper-Free ASJ, Pipe Insulation Owens Corning Insulating S One Owens Corning Parkwa Toledo, OH 43659 1-800-GET-PINK or 1-800-4	lation, SSL-İI® Pipe tro Fibras Pipe Insulat Aislamiento para Tub Systems, LLC 19 138-7465 138-7465	ion, ieria NFPA
Manufacturer Name: Address: Customer Service Phone Number: Health Issues Information: Technical Product Information: Emergency Phone	Pipeshield, SSL® Pipe Insu Insulation, VaporWick®, Vi Evolution [™] Paper-Free ASJ, Pipe Insulation Owens Corning Insulating S One Owens Corning Parkwa Toledo, OH 43659 1-800-GET-PINK or 1-800-4 1-800-GET-PINK or 1-800-4	lation, SSL-İI® Pipe tro Fibras Pipe Insulat Aislamiento para Tub Systems, LLC 19 138-7465 138-7465 138-7465 n ET and weekends)	ion, ieria NFPA
Manufacturer Name: Address: Customer Service Phone Number: Health Issues Information: Technical Product Information: Emergency Phone Number:	Pipeshield, SSL® Pipe Insu Insulation, VaporWick®, Vii Evolution [™] Paper-Free ASJ, Pipe Insulation Owens Corning Insulating S One Owens Corning Parkwa Toledo, OH 43659 1-800-GET-PINK or 1-800-4 1-800-GET-PINK or 1-800-4 1-800-GET-PINK or 1-800-4 1-419-248-5330 (after 5pn	lation, SSL-İI® Pipe tro Fibras Pipe Insulat Aislamiento para Tub Systems, LLC 19 138-7465 138-7465 138-7465 n ET and weekends)	ion, ieria NFPA
Manufacturer Name: Address: Customer Service Phone Number: Health Issues Information: Technical Product Information: Emergency Phone Number: CHEMTREC:	Pipeshield, SSL® Pipe Insu Insulation, VaporWick®, Vii Evolution [™] Paper-Free ASJ, Pipe Insulation Owens Corning Insulating S One Owens Corning Parkwa Toledo, OH 43659 1-800-GET-PINK or 1-800-4 1-800-GET-PINK or 1-800-4 1-419-248-5330 (after 5pn 800-424-9300 (24 hours er	lation, SSL-İI® Pipe tro Fibras Pipe Insulat Aislamiento para Tub Systems, LLC 19 138-7465 138-7465 138-7465 n ET and weekends)	ion, ieria NFPA

SAFETY DATA SHEET

SECTION 2 - HAZARD(S) IDENTIFICATION

Applies to Product

Emergency Overview:	Exposure to dust may be irritating to eyes, nose, and throat.
Route of Exposure:	Eye contact Skin contact Inhalation
Potential Health Effects:	
Eye:	May cause slight irritation.
Skin:	May cause slight skin irritation.
Inhalation:	May cause irritation of respiratory tract.
Ingestion:	Ingestion of this product is unlikely.
Chronic Health Effects:	There is no known chronic health effect connected with long-term use or contact with this product.
Potential Environmental Effects :	There is no known ecological information for this material.
Aggravation of Pre-Existing Conditions:	Chronic respiratory or skin conditions may temporarily worsen from exposure to this product.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS Chemical Name CA S# Ingredient Percent Fiber Glass (Wool) 65997-17-3 60 - 100 by weight Cured Binder N/A 0 - 40 by weight

The remaining components of this product are non-hazardous or are in a small enough quantity as to not meet regulatory thresholds for disclosure. These components contain no substances or impurities which would influence the classification of this product.

SECTION 4 - FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Do not rub or scratch eyes. If eye irritation persists, consult a specialist.
Skin Contact:	Wash off immediately with soap and cold water. DO NOT use warm water because this will open up the pores of the skin, which will cause further penetration of the fibers. Use a wash cloth to help remove fibers. DO NOT rub or scratch affected areas. Remove contaminated clothing. If irritation persists get medical attention. Never use compressed air to remove fibers from the skin. If fibers are seen penetrating from the skin, the fibers can be removed by applying and removing adhesive tape so that the fibers adhere to the tape and are pulled out of the skin.
Inhalation:	Move to fresh air. If symptoms persist, call a physician.
Ingestion:	Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal blockage does not occur. Rinse mouth with water and drink water to remove fibers from the throat. If symptoms persist, call a physician.
Note to Physicians:	Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties:	Non Flammable.
Flash Point:	Does not apply.
Auto Ignition Temperature:	Does not apply.
Extinguishing Media:	dry chemical foam carbon dioxide (CO2) water fog
Protective Equipment:	Wear self-contained breathing apparatus (SCBA) and full fire fighting protective gear.
Unusual Fire Hazards:	Hydrogen chloride to be released from the PVC barrier and vinyl facings during a fire.
Hazardous Combustion Byproducts:	Carbon monoxide. Carbon dioxide. Ammonia. Other undetermined compounds could be released in small quantities.
Universal Fire And Explosion Hazards:	Not available.

NFPA	Ratings:

NFPA Health:	2
NFPA Flammability:	1
NFPA Reactivity:	0
NFPA Other:	

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions:	Avoid contact with skin and eyes.
Environmental Precautions:	Prevent further leakage or spillage if safe to do so.
Methods for containment:	This material will settle out of the air. Prevent from spreading by covering, diking or other means.
Methods for cleanup:	Use an industrial vacuum cleaner with a high efficiency filter to clean up dust and fiber contamination. Avoid dry sweeping. Pick up and transfer to properly labeled containers.
Other Precautions:	Does not apply.

SECTION 7 - HANDLING and STORAGE

Handling:

Avoid dust formation. Do not breathe dust.

	Wear personal protective equipment.
Storage:	Keep product in its packaging until use to minimize potential dust generation. Product should be kept dry and undercover.
Hygiene Practices:	Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing before re-use.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Provide local exhaust and/or general ventilation to maintain exposure below regulatory and recommended limits. Dust collection system must be used in transferring operations, cutting or machining or other dust generating processes, such as using power tools. Vacuum or wet clean-up methods should be used.
Eye/Face Protection:	Safety glasses with side-shields.
Skin Protection Description:	Protective gloves. Long sleeved shirt and long pants.
Respiratory Protection:	When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.
Other Protective :	When the temperature of the surface being insulated exceeds 250°F (121°C), including initial startup, the binder in these products may undergo various degrees of decomposition depending on the temperature in the application. The need for respiratory protection will vary according to the airborne concentration of the decomposition products released and accumulated in the area. Wear the appropriate respiratory protection according to the conditions and exposure levels in the area.

EXPOSURE GUIDELINES

Ingredient	Guideline OSHA	Guideline ACGIH	Ontario Canada	Mexico
Fiber Glass (Wool)	TLV-TWA: 1 f/cc (Respirable)	TLV-TWA: 1 f/cc (Respirable)	TWAEV-TWA: 0.05 mg/m3 or 1 f/cc STEL: 0.6 mg/m3	TWA: 0.15 mg/m3

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance:	Tan with or without jacket of paper or aluminized plastic film.
Color:	Tan
Odor:	Faint resin odor.
Boiling Point:	No Data
Melting Point:	No Data
Specific Gravity:	No Data
Solubility:	Insoluble in water.
Vapor Density:	No Data
Vapor Pressure:	No Data
Evaporation Rate:	No Data
pH:	No Data
Viscosity:	No Data
Flash Point:	Does not apply.
Auto Ignition Temperature:	Does not apply.

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability:	Stable under normal conditions.
Hazardous Polymerization:	Hazardous polymerization does not occur.
Conditions to Avoid:	None expected
Incompatible Materials:	No materials to be especially mentioned.
Special Decomposition Products:	See Section 5 of MSDS for hazardous decomposition products during a fire.

SECTION 11 - TOXICOLOGICAL INFORMATION

Dusts may cause mechanical irritation to eyes and skin. Ingestion may cause transient irritation of throat, stomach and gastrointestinal tract. Inhalation may cause coughing, nose and throat irritation, and sneezing. High exposures may cause difficulty breathing, congestion, and chest tightness.

Carcinogens:						
	ACGIH			IARC	Canada	MEXICO
Fiber Glass (Wool)	A3 Animal Carcinogen			Group 3 - Not Classifiable as to its Carcinogenicity to Humans.		A3 Animal Carcinogen
Cured Binder	No Data			No Data		No Data

Applies to Product :

Sensitization:	No information available.
Mutagenicity:	No information available.
Reproductive Toxicity:	No information available.
Teratogenicity:	No information available.
Neurological Effects:	No information available.
Fiber Glass (Wool):	
Chronic Effects:	In June 2011, The National Toxicology Program (NTP) removed biosoluble glass wool fibers from its list of possible carcinogens used for home and building insulation. In October 2001, the International Agency for Research on Cancer (IARC) classified fiber glass wool as Group 3,"not classifiable as to its carcinogenicity to humans". The 2001 decision was based on human studies and animal research that have not shown an association between inhalation exposure to dust from fiber glass wool and the development of respiratory disease.
Cured Binder :	
Ingestion:	Ingestion - Rat LD50: 7 gm/kg - [Autonomic Nervous System - Other (direct) parasympathomimetic Behavioral - Muscle weakness Lungs, Thorax, or Respiration - Respiratory depression](RTECS)
Acute Toxicity	

SECTION 12 - ECOLOGICAL INFORMATION

Applies to Product :

Ecotoxicity:	This material is not expected to cause harm to animals, plants or fish.
Environmental Stability:	Not available.
Environmental Fate:	Not available.
Bioaccumulation:	Not available.
Biodegradation:	Not available.
Mobility In Environmental Media:	Not available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Applies to Product :

Waste Disposal:

Dispose of in accordance with Local, State, Federal and Provincial regulations.

SECTION 14 - TRANSPORT INFORMATION

IATA Shipping Name:	Not Regulated.

MEX Shipping Name : Not Regulated.

SECTION 15 - REGULATORY INFORMATION

Inventory Status

	Japan ENCS	Philippines PICCS	China	South Korea KECL	Australia AICS
Fiber Glass (Wool)	Not listed	Listed	Listed	KE-17630	Listed
Cured Binder	Not listed		Listed	KE-35185	Listed

Г

Т

	Status		
Fiber Glass (Wool)	Listed		
Cured Binder	Listed		

SECTION 16 - ADDITIONAL INFORMATION

SDS Creation Date:	May 16, 1995
SDS Revision Date:	January 14, 2013
MSDS Revision Notes:	Section 11 Updated with 2011 NTP Evaluation
Disclaimer:	Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.

Copyright© 1996-2011 Actio Corporation. All Rights Reserved.